## **AMENDMENTS TO THE CLAIMS**

1. (currently amended) A method for establishing a connection with a mobile node, the method comprising:

receiving a registration request;

determining a tunnel identifier, wherein the tunnel identifier is independent of (i) a home address of the mobile node and (ii) an address of a home agent;

transmitting the registration request to the home agent, the registration request including the tunnel identifier;

receiving a response to the request and, responsively, activating a connection;

receiving data packets from the home agent in response to transmitting the registration request, the data packets including the tunnel identifier;

using the tunnel identifier comprises using the tunnel identifier to identifying the connection using the tunnel identifier comprises using the tunnel identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify an entry in a connection table, wherein the entry in the connection table identifies the connection; and

routing the packets along the connection.

- 2. (previously presented) The method of claim 1 wherein the data packets received from the home agent include a header and the header includes the tunnel identifier.
  - 3. (canceled)
  - 4. (canceled)

5. (currently amended) A method for establishing a connection with a mobile node, the method comprising:

receiving a registration request from a mobile node, the mobile node having a home agent, the registration request also representing a call;

assigning a tunnel identifier to the call associated with the registration request, wherein the tunnel identifier is independent of (i) a home address of the mobile node and (ii) an address of the home agent;

forwarding the registration request to the home agent, the request including the tunnel identifier;

establishing a connection;

receiving a registration response and forwarding the registration response to the mobile node;

receiving packets of data from the home agent, each of the packets of data including the tunnel identifier; and

subsequently, using the tunnel identifier to identify the connection for packets having the tunnel identifier, wherein using the tunnel identifier to identify the connection for packets having the tunnel identifier comprises using the tunnel identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify an entry in a connection table, wherein the entry in the connection table identifies the connection.

6. (canceled)

- 7. (currently amended) The method of claim 5 [[6]] wherein the connection information is from the point-to-point protocol (PPP).
- 8. (previously presented) The method of claim 5 wherein each of the packets includes a header and the header is a Generic Routing Encapsulation (GRE) header.
  - 9. (currently amended) A method comprising:

receiving a registration request;

receiving a data stream, the data stream associated with the registration request, the data stream including a plurality of packets;

assigning an identifier to the data stream, wherein the identifier is independent of (i) a home address of a mobile node and (ii) an address of a home agent for the mobile node;

transmitting the registration request to the home agent, the registration request including the identifier;

receiving return packets of information, the return packets of information including the identifier; and

translating the identifier into a connection and transmitting the return packets using the connection, wherein translating the identifier into the connection comprises using the identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify an entry in a connection table, wherein the entry in the connection table identifies the connection.

10. (currently amended) The method of claim 9 wherein the step of translating includes establishing the [[a]] tunnel table, the tunnel table having entries corresponding to

tunnel identifiers.

11. (currently amended) The method of claim 10 wherein the step of translating

includes establishing the [[a]] connection table, the connection table including connection

information for entries in the tunnel table.

12. (previously presented) The method of claim 11 wherein the connection

table includes information according to the point-to-point protocol (PPP) format.

13. (currently amended) A system comprising:

a mobile node;

a packet data-switching node (PDSN), the PDSN communicatively coupled to the mobile

node, the PDSN receiving a registration request from the mobile node, the PDSN assigning a

tunnel identifier to a plurality of packets received from the mobile node;

a home agent coupled to the PDSN, the home agent receiving and storing the tunnel

identifier in the registration request and sending return packets to the PDSN including the tunnel

identifier;

wherein the tunnel identifier is independent of (i) a home address of the mobile node and

(ii) an address of the home agent;

wherein the PDSN receives a response message from the home agent and establishes a

connection between the mobile node and the home agent; and

wherein the PDSN extracts the tunnel identifier from the return packets and translates the tunnel identifier into information representative of the connection, and transmits the return packets on the connection, wherein the PDSN translating the tunnel identifier into information representative of the connection comprises the PDSN using the tunnel identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify an entry in a connection table, wherein the entry in the connection table identifies the connection.

- 14. (original) The system of claim 13 wherein the tunnel identifier is included in a header in the return packets.
- 15. (original) The system of claim 13 wherein the connection is made according to the point-to-point protocol (PPP).
- 16. (currently amended) The system of claim 13 wherein the PDSN includes the [[a]] tunnel [[entry]] table and the connection table, and wherein the connection table is a point-to-point protocol (PPP) connection table.
- 17. (currently amended) A system for establishing a connection with a mobile node, the system comprising:

means for receiving a registration request;

means for determining a tunnel identifier, wherein the tunnel identifier is independent of

(i) a home address of the mobile node and (ii) an address of a home agent;

means for transmitting the registration request to the home agent, the registration request including the tunnel identifier;

means for receiving a response to the request and, responsively, activating a connection;

means for receiving data packets from the home agent in response to transmitting the

registration request, the data packets including the tunnel identifier;

means for identifying the connection using the tunnel identifier, wherein identifying the

connection using the tunnel identifier comprises using the tunnel identifier to identify an entry in

a tunnel table and using the entry in the tunnel table to identify an entry in a connection table,

wherein the entry in the connection table identifies the connection; and

means for routing the packets along the connection.

18. (previously presented) The system of claim 17 wherein the data packets

received from the home agent include a header and the header includes the tunnel identifier.

19. (canceled)

20. (canceled)

21. (currently amended) A system for establishing a connection with a mobile node,

the system comprising:

means for receiving a registration request from a mobile node, the mobile node having a

home agent, the registration request also representing a call;

means for assigning a tunnel identifier to the call associated with the registration request,

wherein the tunnel identifier is independent of (i) a home address of the mobile node and (ii) an

address of the home agent;

means for forwarding the registration request to the home agent, the request including the tunnel identifier;

means for establishing a connection;

means for receiving a registration response and forwarding the registration response to the mobile node;

means for receiving packets of data from the home agent, each of the packets of data including the tunnel identifier; and

means for using the tunnel identifier to identify the connection for packets having the tunnel identifier, wherein using the tunnel identifier to identify the connection for packets having the tunnel identifier comprises using the tunnel identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify an entry in a connection table, wherein the entry in the connection table identifies the connection.

## 22. (currently amended) A system comprising:

means for receiving a registration request;

means for receiving a data stream, the data stream associated with the registration request, the data stream including a plurality of packets;

means for assigning an identifier to the data stream, wherein the identifier is independent of (i) a home address of a mobile node and (ii) an address of a home agent for the mobile node;

means for transmitting the registration request to a home agent, the registration request including the identifier;

means for receiving return packets of information, the return packets of information including the identifier; and

means for translating the identifier into a connection and transmitting the return packets

using the connection, wherein translating the identifier into the connection comprises using the

identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify

an entry in a connection table, wherein the entry in the connection table identifies the connection.

23. (currently amended) A computer readable medium having stored therein

instructions for causing a processing unit to execute the following method:

receiving a registration request;

determining a tunnel identifier, wherein the tunnel identifier is independent of (i) a home

address of a mobile node and (ii) an address of a home agent;

transmitting the registration request to the home agent, the registration request including

the tunnel identifier;

receiving a response to the request and, responsively, activating a connection;

receiving data packets from the home agent in response to transmitting the registration

request, the data packets including the tunnel identifier;

identifying the connection using the tunnel identifier, wherein identifying the connection

using the tunnel identifier comprises using the tunnel identifier to identify an entry in a tunnel

table and using the entry in the tunnel table to identify an entry in a connection table, wherein the

entry in the connection table identifies the connection; and

routing the packets along the connection.

24. (currently amended) A computer program for establishing a connection between a mobile node and a home agent, the program comprising:

first code for receiving a registration request;

second code for determining a tunnel identifier, wherein the tunnel identifier is independent of (i) a home address of the mobile node and (ii) an address of the home agent;

third code for transmitting the registration request to the home agent, the registration request including the tunnel identifier;

fourth code for receiving a response to the request and, responsively, activating a connection;

fifth code for receiving data packets from the home agent in response to transmitting the registration request, the data packets including the tunnel identifier;

sixth code for identifying the connection using the tunnel identifier, wherein identifying the connection using the tunnel identifier comprises using the tunnel identifier to identify an entry in a tunnel table and using the entry in the tunnel table to identify an entry in a connection table, wherein the entry in the connection table identifies the connection; and

seventh code for routing the packets along the connection.